

HIGH PRESSURE JET



HPJ (LAVOR)-160



HPJ (LAVOR)-150(P)



HPJ-150



HPJ-200

Technical Specification	HPJ-160 (Lavor)	HPJ-150 (P) (Lavor)	HPJ -150 (C)	HPJ -200 (C)
Max Pressure (Bar)	160	150	150	200
Working Pressure (Bar)	140	150	110	180
Power (Hz)	1Ø	1Ø	1Ø	3Ø
Voltage(V)	230	230	230	400
Volume Discharge L/Min	7	9	8	12
Inlet Water Temp (°C)	50	50	50	50
Absorbed Power(W)	2200	2800	2250	3750
RPM	1450	2800	2800	1450

STEAM CLEANER



LAVOR-GV KONE

Technical Specification	Lavor GV Kone	Lavor GV Katla
Power Supply (V)	230V-50Hz	230V-50Hz
Max. Steam Pressure (Bar)	4	9
Max. Temperature (°C)	145	175
Absorbed Power (W)	230V, 2000W	230V, 3300W
Tank Capacity (L)	1.5	2X5
Hose Pipe Length (M)	2.5	3



LAVOR-GV KATLA



CLEANOTECH INDIA
MANUFACTURER OF CLEANING PRODUCTS



F-24, FIRST FLOOR, SECTOR 09, NOIDA (U.P.)

Mob.: 9999822726 | 8826608820 | E-mail: cleanotechindia@gmail.com

DEALS IN ALL FLOOR CLEANING MACHINES SERVICES AND SALES

VACUUM CLEANERS



CTI-15 CTI-30 CTI-60 CTI-70 CTI-80 CTI-400

TECH. SPEC.	CTI-15	CTI-30	CTI-60	CTI-70	CTI-80	CTI-400
Max Watt (W)	1000	1200	2400	2400	3600	3730
Power Supply (V)	230V-50Hz	230V-50Hz	230V-50Hz	230V-50Hz	230V-50Hz	400V-50Hz
Suction mm H ₂ O	1800	2200	2350	2000	3000	3365
Air Flow m ³ /hr.	140	170	216	382	432	594
Tank Capacity Ltrs.	15	30	60	70	80	50
Noise Level (DB)	65	65	65	68	70	65
Power Cord (M)	10	10	15	8	8	15

AUTO SCRUBBER DRIERS



CTIAD/40 CTIAD/50 ASD-25 ASD-50

TECHNICAL SPECIFICATIONS	CTIAD/40	CTIAD/50	ASD-25	ASD-50
Scrubbing Width (mm)	455	510	430	530
Squeegee Width (mm)	755	755	860	860
Brush Speed (rpm)	148	210	280	180
Solution Tank (ltrs.)	40	50	30	60
Recovery Tank (ltrs.)	31	40	30	60
Vacuum (mm H ₂ O)	50	50	2200	2200
Area Coverage (Sq. mt./hr)	1750	1750	1700	2200
Weight (kgs.) (Appx.)	80	108	80	110
Power Supply (V)	230V-50Hz	230V-50Hz	230V-50Hz	230V-50Hz

SINGLE DISC



CTISD/55 CTISD/45 CTISD/47

TECHNICAL SPECIFICATIONS	CTISD/55	CTISD/45	CTISD/47
Power Supply (V)	230V-50Hz	230V-50Hz	230V-50Hz
Brush Dia (mm)	432	432	500
Power Cons. (W)	1800	1500	1500
Brush Speed (rpm)	154	165	165
Weight (kgs.)	55	45	49
Brush Pressure (kgs.)	40	42	50
Cable Length(Mtr.)	12	12	12
Area Coverage m ² /h	480	480	480
Tank Capacity (Ltrs)	10	12	12

HAND SCRUBBERS



Technical Specifications	Hand Scrubber	Mini Polisher
Voltage (V)	230	220
Brush Dia (mm)	150	180
Power Cons. (W)	550	1200
Brush Speed (rpm)	1250	600-3000
Weight (kgs.)	2	3

RIDE ON SCRUBBER DRIERS



COMFORT-XXS-66B COMFORT-XS-75R

TECHNICAL SPECIFICATIONS	COMFORT-XXS-66B	COMFORT-XS-75R
Brush Motor (W)	2X400	2X400
Vacuum Motor (W)	1000	1000
Brush Dia (mm)	660	750
Fresh Tank	75	110
Productivity (m ² /Hr)	3250	3750
Squeegee Width (mm)	855	900
Weight (Kg.)	160	223
Power (W)	2000	2000
IP Protection	IPX4	IPX4
Voltage	24	24
Capacity Tank (ltrs)	75	130

RIDE ON SWEEPER



TRS 1300

Technical Specification	Ride On TRS1300
Cleaning Width (mm)	1300
Hopper Capacity (L) 40	120
Hopper Unloading 25	Manual
Filtering Surface (m ²)	5
Installed Power (W) -	1200
Engine/ Power (V)	48
Batteries (V)	48
Weight (Kg)	550
Dimensions (mm)	1550x1400x1300
Cleaning Area (m ² /h)	9100