

Deepshikha Castings Pvt. Ltd. is one of the leading manufacturers of DUCTILE IRON FLANGED PIPES in Central India. With an intention to provide all the products, related to waterline under one roof, we are now manufacturing products like CI Flanged Pipes, CI Spun Pipes (S & S), CI Fittings, CI Man Hole Covers, CI Earthing Pipes, CI Surface Box, CI Foot Steps, Cowl Pipes and CI Engineering Castings for all Industrial Sectors and Agriculture Sectors. Our dedicated team acquired the much-needed exposure of work and technical know-how to provide superior quality of all the above products and timely services to our customers.

Ductile Iron **Double Flanged Pipe**

(As per IS 8329:2000)

DI FLANGE PIPE RANGE

SIZE- DN (mm)	LENGTH	PRESSURE RATING	CLASS OF PIPE	JOINT
80-600	Available in Mix & standard length up to 5.5/6 Mtr	PN 10 & PN 16	K9	Flanged Joint

FLANGING TECHNOLOGY

Screwing and Welding Technology.

Dimensions and Tolerances: As Per IS 8329:2000

COATING

All pipes are coated internally with cement mortar lining and bituminous coating externally as per customer requirements and specification.

APPLICATIONS

• Water, Sewage & Waste Water System • Vertical pipe lines for overhead tanks • Elevated Services Reservoir (ESR)

OUR MANUFACTURING FITTINGS PRODUCT RANGE















Tee

Collar

Adaptor

Cowl Pipe

Surface Box

Dismantle Joint

MECHANICAL PROPERTIES: AS PER IS 8329:2000

		Elongation	
Size-DN (mm)	Tensile	at break	Hardness
	Strength (Min)	(Min)	(Max)
Pipe 80-600mm	420 Mpa	10%	230HB
Flange	420 Mpa	5%	250HB

HYDROSTATIC TEST PRESSURE AT WORKS (MPA):

DN (mm)	PN 10	PN 16	PN 25	PN 40
80-600	1.6	2.5	3.2	4.0

ACCESSORIES FOR FLANGED PIPES

GASKET: For Flanged pipe jointing, flat rubber gasket as per IS 638 are used.

*We should used Ethylene Propylene Diene Monomer (EPDM) OR Styrene Butadiene Rubber (SBR)

NUT & BOLTS: Galvanized Nuts & Bolts made of Mild Steel as per IS 1367 is recommended for jointing two flanges. The bolt dimension should be as per IS 1364.



Size-DN (mm)

CI Pipe 80-300

CI Pipe 350-600

Flange

Size-DN (mm) 80-300

350-600

CAST IRON DOUBLE FLANGED PIPE (As Per IS 1536: 2001)

CIDF PIPE RANGE

SIZE- DN (mm)	LENGTH	CLASS OF PIPE	JOINT	FLANGE TECHNOLOGY
80mm to 600mm	Available in Mix & standard length up to 5.5 Mtr	Class B	Flanged Joint	Screwing

Dimensions and Tolerances: As per IS 1536:2001

APPLICATIONS Ash Handling system in Power Plants and Steel Plants. Drinking Water and Industrial Purpose Sulphur Acid Plants

 Chemical handling like Soda Ash Plants. Fertilizer Plants
Vertical Pipe Lines for overhead Tanks / Elevated Service Reservoir (ESR)

OUR MANUFACTURING PRODUCT RANGE 'DEEPSHIKHA' C.I. & D.I. Centrifugally Cast (Spun) Iron Pressure Pipe IS:1536(ISI Mark) Engineering Cast Iron **Double Flanged** Cast Iron Earthing Cast Iron Manhole Castings **Kitchen Utensils** Pipes & Fittings Electrode Cover (ISI Mark)



Deepshikha- The Water line solutions An ISO 9001-2015 certified Company Corporate Office: B-2, 623/A, 'Chandradina', Mehadia Square, Chhoti Dhantoli, Nagpur- 440012 Mob: 9822474131, 7219612530, 9822558131 Email- deepshikha_castings@yahoo.in

Works: 116/1, Mouza- Nagalwadi, Near Waddhamna, Amravati road Tah- Hingna, Nagpur- 440023



MECHANICAL PROPERTIES: AS PER IS 1536:2001

Tensile

Strength (Min)

-

200

150

Hydrostatic Test Pressure

2.5 Mpa 1.6 Mpa

Hardness

(Max)

230HB

230HB

230HB

Ring Test

(Min)

390 Mpa

-

HYDROSTATIC TEST PRESSURE AT WORKS (MPA):

www.deepshikhacastings.com www.deepshikhacastings.in