



UNITED MACHINES

TUMBLE DRYER

Technology - Performance - Savings



UNITED MACHINES INDIA PVT LTD

www.unitedmachines.com

Fully Automatic Tumble Dryer

Our extensive range of Dryers have been developed to fulfill the professional laundry requirements of customers and to ensure high productivity with a minimal use of energy.

Fully made by high grade stainless steel to avoid rust formation thus ensures the long life of the machine.

Ultra Fast Dry

When faster dry times are your top priority, the only solution is GZZ/GDZ models. We've matched energy input with airflow and included a 10" exhaust vent to provide 20% faster drying.

Lower Utility and Labor Costs

Our tumblers achieve the perfect balance between drying temperature, airflow pattern and usable cylinder space for maximum energy efficiency, shortening drying times - and reducing your utility and labor costs.

Easy access:

All vital parts have easy access from the front and rear for simple servicing. The drum suspension is Sturdy and has double sealed bearings and belt drive. In the front of the drum, two supporting rollers increase the stability of the drum.

Customized user panels

Customized user panels ensure the perfect solution for your specific needs. Temperature, time, programme, reverse drum action on/off and adjustment of cool down for easy operation can be Individually selected.

Easy loading and unloading:

The large diameter of the door opening on our tumble dryers ensures easy loading and unloading. For maximum accessibility, the door opens to nearly 180°.

Item Name	Unit	GZZ GDZ -15	GZZ GDZ -25	GZZ GDZ -50	GZZ GDZ -50B	GZZ GDZ -100	GZZ GDZ -100Q
Rated capacity (Dry loading per cycle)	Kg	15	25	50	50	100	100
Drum DXL	mm	780x650	930x800	1200x946	1160x1000	1460x1180	1460x1180
Power supply	V/P/Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50
Power of main motor	Kw	0.55	0.75	1.5	1.5	3	3
Fan Motor	Kw	0.37	0.75	1.5	1.5	2x1.5	2x1.5
Drum speed	rpm	45	35	32	32	30	30
Steam pressure	mpa	0.5-0.6	0.5-0.6	0.5-0.6	0.5-0.6	0.5-0.6	0.5-0.6
Steam pipe (DN)	mm	Dn20	Dn25	Dn25	Dn25	Dn25	Dn40
Steam trap pipe (DN)	mm	Dn15	Dn25	Dn25	Dn20	Dn25	Dn25
Power consumption per cycle	kw.h	0.5	0.9	1.8	1.8	3.2	3.2
Steam consumption per cycle	Kg	18-25	25-30	80-90	50-60	130-160	130-160
Power of heater	Kw	14.4	23.4	39	39		
Power consumption per cycle	Kw.h	9	15	29	29		
Dimension of air exhaust port	mm	170x170	230x270	270X350	280x350	330x400	330x400
Dimension (LxWxH)	mm	1150x870x1450	1270x1023x1760	1500x1265x2185	1570x1282x2070	1915x1610x2300	2100x1600x2560
Machine weight (without package)	kg	310	450	800	800	1600	1700

UNITED MACHINES INDIA PVT LTD

23, Ramaiah Colony 2nd Street East, Tirupur - 641602. Tamilnadu - INDIA.

Ph : 0091-421-4331010 (10 Lines.)

Ph : 0091-421-4330505 (10 Lines.)

Ph : 0091-421-4336006 (10 Lines.)

Fax : 0091-421-2231537, 2231327.

E-mail : laundry@unitedmachines.com

Web : www.unitedmachines.com