Techno Flameproof Control Manufacturers of Flameproof & Weatherproof Equipments

Catalogue 2018



Company Profile

Techno Flameproof Control that has been in business of manufacturing flameproof & weatherproof Equipments for past 5 Years. We also offer customised LED lighting solution to new as well as existing units. Our products are CMRI certified products which includes Well glass fittings, Clean room fittings, Bulkhead fittings, Tube light fittings, Flood light fittings, Vessel lamps, Junction box & Cable glands. We have been an established and popular company with an excellent track record for the best customer satisfaction. We have never compromised on the quality and the services provided to the customer. We believe in keeping the customers happy and providing them with products at a very competent price. We have an excellent staffs who will guide you with their best ideas by keeping in constant touch with your company and informing about the upcoming products and latest technology. Our all functions carried out are in-house and our products are designed to confirm all applicable standards.



Products



FLP LED Light Fitting



FLP Switch Gears



FLP Tube light Fitting

FLP Junction Box



FLP Panels



Cable Glands

LED Light Fitting (FLP)



Type No. : TWL-412160 Series Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.IIA, IIB, IP-66 Area Classification : Industrial Safe area. **Transparent Part : Heat & Impact resistant toughened clear glass Lens.** Power Supply (Driver) : Constant current with pf > 0.95 & THD < 15% Light Source : COB LED (CITIZEN Make) Input Voltage : 142V TO 270V AC Colour Temp. (CT) : 3500 K | 4500 K | 5500 K Lumen per Watt : 110 lm | +- 5% Light Colour : Bright White Cool Light Life of LED : 50,000 HRS BH Beam Angle : 90 ° | 120 ° Wattage Available : Up to 160 Watt Variants Available : As per clients requirement in specified wattage

Tube light (FLP)





Type No. : TFC-TL-FLP Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.II A, B, C IP-66 Area Classification : Industrial Safe area. Transparent Part : Heat & Impact resistant toughened clear glass. Power Supply (Driver) : Constant current with pf > 0.95 & THD < 15% Light Source : SMD LED (OSRAM Make) Input Voltage : 142V TO 270V AC Colour Temp. (CT) : 3500 K | 4500 K | 5500 K Lumen per Watt : 110 Im | +- 5% Light Colour : Bright White Cool Light Life of LED : 50,000 HRS Wattage Available : Up to 50 Watt Variants Available : As per clients requirement in specified wattage

Junction Box (FLP)





TM

Type No. : TFC-JB-FLP Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.II A, B, C IP-66 Area Classification : Industrial Safe area. Variants Available : As per clients requirement in specified dimensions



Switch Gears (FLP)





Type No. : TFC-SG-FLP Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.II A, B, C IP-66 Area Classification : Industrial Safe area. Variants Available : As per clients requirement in specified dimensions

LED Light Fitting (FLP)





Type No. : TWL-412160 Series Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.IIA, IIB, IP-66 Area Classification : Industrial Safe area. **Transparent Part : Heat & Impact resistant toughened clear glass Lens.** Power Supply (Driver) : Constant current with pf > 0.95 & THD < 15% Light Source : COB LED (CITIZEN Make) Input Voltage : 142V TO 270V AC Colour Temp. (CT) : 3500 K | 4500 K | 5500 K Lumen per Watt : 110 lm | +- 5% Light Colour : Bright White Cool Light Life of LED : 50,000 HRS BH Beam Angle : 90 ° | 120 ° Wattage Available : Up to 60 Watt Variants Available : As per clients requirement in specified wattage



Control Panel (FLP)





Type No. : TFC-CP-FLP Enclosure : Cast Aluminium LM6 Enclosure. Protection : Ex-d Zone 1 & 2 Gas Gr.II A, IIB, IP-66 Area Classification : Industrial Safe area. Variants Available : As per clients requirement in specified dimensions



Cable Glands (FLP/NON FLP)





Type No. : TFC-IPF Material : Brass (IS 319) | AL | MS | SS Finish : Nickel plated Standards. Threads : ET" | BSC Standards Sealing Ring : Neoprene Ref Standard : IS | IEC 60529:2001 Protection : IP-66 as per IS | IEC 60079-0:2004 CMRI Cert. No : CIMFR/TC/P/H 434 ISI Cert. No : CM/L-2849678 PESO Cert. No : P338415/1 Area Classification : Flammable Gas | Vapour Area(Gas I, IIA, IIB) Variants Available : As per clients requirement in specified dimensions



Corporate Office & Works

664, GIDC Ind. Estate, Makarpura Vadodara – 390010- (Gujarat)

<u>Talk To Us!!</u> +91 98259 39941 | +91 98259 39303 tfcindia91@gmail.com





