

Powerstick®

# PRODUCT CATALOG



[WWW.POWERSTICKADHESIVE.COM](http://WWW.POWERSTICKADHESIVE.COM)

ADDRESS : KATHWADA GIDC AHMEDABAD GUJARAT 382430.

PHONE +91-6355-901-960



**PATEL**  
ENTERPRISE

# Power stick®



# Power stick®



## PRODUCT FEATURES

Type	Power Stick Instant Glue (LV)
Description	Power Stick Instant Glue(LV) Quick Setting Cyanoacrylate Adhesive Easy To Use.
Application	Metal, Ceramic, Stone, Leather, Helmet, Rubber, Handicrafts, Wood, Polycarbonate, Acrylic, Toys, Plastics, Furniture, LED Board, Shoes, Glass etc.
Cure speed	2-5 Seconds
Viscosity	2-3 CPS
SHELF LIFE	12- Months
Product Sizes	20 GM , 50 GM
Note	Store In Cool & Dry Dark Place (20°C Below)



# Power stick®



## PRODUCT FEATURES

Type	Power Stick Super Glue (502)
Description	Power Stick Super Glue(502) Quick Setting Cyanoacrylate Adhesive Easy To Use.
Application	PVC Furniture, Metals, Wood, Stone, Helmet, Rubber, Toys, Handicrafts, Plastics, Ceramics, Glass, Leathers, Polycarbonate Etc.
Cure speed	2-5 Seconds
Viscosity	2-3 CPS
SHELF LIFE	12- Months
Product Sizes	20 GM , 50 GM
Note	Store In Cool & Dry Dark Place (20°C Below)



# Power stick®



## PRODUCT FEATURES

Type	Power Stick Gel Glue(HV)
Description	Power Stick Gel Glue(HV) Super Strong Instant Adhesive Easy To Use.
Application	Wood, Rubber, WPC/PVC, MDF Board, Mica, Plastic, Metal, Fabric, Flex, Marble, 3D Fonts, Stone, Ceramics, HD HMR Etc.
Cure speed	20-25 Seconds
Viscosity	1500-1600 CPS
SHELF LIFE	12- Months
Product Sizes	50 GM, 125 GM, 250 GM, 500 GM.
Note	Store In Cool & Dry Dark Place (20°C Below)

# Power stick®



## PRODUCT FEATURES

Type

Power Stick Flex Glue

Description

Power Stick Flex Glue Fast Setting Easy To Use.

Application

Vinyl Flex Glue, Model Making Adhesive, Glue For Screen Printing Frame, Architectural Use & Different Industrial Use.

Cure speed

2-5 Seconds

Viscosity

2-3 CPS

SHELF LIFE

3 Months TO 9 Months

Product Sizes

12 GM, 20 GM, 50 GM

Note

Store In Cool & Dry Dark Place (20°C Below)

# Power stick®

## POWERSTICK CPVC Solvent Cement



### TECHNICAL SPECIFICATION

#### Heavy Duty Medium Setting.

LoVOC CPVC cement for all classes and schedules with interference fit through 12" (315 mm) diameter.

Industrial Quality for Non-Chemical Applications up to 180°F (82°C).

Approved for use on CPVC Piping Systems.

Recommended Application Temperature 0°F to 115°F / -17°C to 46°C.

### AVAILABLE PACK SIZE

- 10 ml Tube, 25ml Tube,
- 59 ml Tin, 118 ml Tin,
- 237 ml Tin, 500 ml Tin,
- 1 Ltr Tin.



# Power stick®

## **POWERSTICK PVC Solvent Cement**



### **TECHNICAL SPECIFICATION**

**POWERSTICK Heavy Duty Clear cement for use on all schedules and classes PVC pipe and fitting up to 12" diameter for non pressure pipe**

**Heavy Bodied, Fastset**

**Thick formula fills gaps in large diameter pipe and loose fitting joints.**

**Recommended for potable water, non pressure pipe, SWR/rigid pipes and DWV.**

**Recommended application temperature 40°F to 110°F / 4°C to 43°C.**

### **AVAILABLE PACK SIZE**

- 10 ml Tube, 25ml Tube,
- 59 ml Tin, 118 ml Tin,
- 237 ml Tin, 500 ml Tin,
- 1 Ltr Tin.

# Power stick®

## POWERSTICK UPVC Solvent Cement



### TECHNICAL SPECIFICATION

**Heavy Duty, fast setting PVC cement for all classes and schedules with interference fit through 6" (160 mm) diameter, Schedule 80 through 4" (110 mm) diameter.**

**Quality formulation for irrigation, electrical conduit, pool & spa.**

**Plumbing, including PVC foam core pipe.**

**Can be used without primer on non-pressure systems if local codes permit.**

### AVAILABLE PACK SIZE

- 59 ml Tin, 118 ml Tin,
- 237 ml Tin, 500 ml Tin,
- 1 Ltr Tin.



Power stick®

**WE HELP**  
**GROW YOUR**  
**DISTIBUTERSHIP**



[WWW.POWERSTICKADHESIVE.COM](http://WWW.POWERSTICKADHESIVE.COM)

ADDRESS : KATHWADA GIDC AHMEDABAD GUJARAT 382430.

PHONE +91-6355-901-960

