

## **SEMI AUTOMATIC**

## THERMAL LAMINATOR

## **Compact - Convenient - Fast**





Digital precision display, 9 speed adjustment, convenient to wear film and unskilled personnel operation, high speed, processing efficiency is improved significantly



Steel roller diameter 79mm., Good thermal conductivity, Rapid temperature rise, Film delicate high temperature resistance and durable.



This machine have Gravity tensile anti-coiling design, effectively solve the problem of different thickness of single surface coating curling.

Cold, Single & Double side
79mm.
80g to 350g
5-10m.
340mm.
Digital display
Manual
Gravity stretch
5.5 A
50 HZ
45kg.
690*640*550mm.

Heating mode	Steel roller
Coating tempreature	70-110°C
Membrane core diameter	1 - 3 Inch
Film covering speed	1-3m./minute
Control mode	Key tempreture control
Pressure mode	Spring pressure
Dashed line function	Perforating knife
Trimming function	Automatic
Voltage	220V
Humidity	20%-70%
Gross weight	51kg.
Packaging type	Packed in carton

National Strategic Partner & Distributor in India



PENDRA ROAD, BILASPUR, Chhattisgarh, India 495117 www.digitalprintsolutions.in | www.digitalprint.net.in

— Authorised Channel Partner —