

FLOWRISE GATE VALVE

BS 1414/BS 5154/BS 5352/BS6755/
ASME B 16.34/API 600/API 602/
API 6D/API 598

STAINLESS STEEL (BAR STOCK)

RATING : 150 / 300 #
SIZE : 8 MM TO 100 MM

FORGED CARBON STEEL

RATING : 800 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM
RATING : 150 / 300 #
SIZE : 15 MM TO 50 MM

FORGED STAINLESS STEEL

RATING : 800 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM
RATING : 150 #
SIZE : 15 MM TO 50 MM

CAST IRON

RATING : 125 / 150 #
SIZE : 25 MM TO 600 MM



CAST CARBON STEEL

RATING : 150 #
SIZE : 25 MM TO 600 MM
RATING : 300 #
SIZE : 25 MM TO 400 MM
RATING : 600 #
SIZE : 40 MM TO 400 MM
RATING : 900 #
SIZE : 50 MM TO 200 MM

CAST STAINLESS STEEL/ALLOY STEEL

RATING : 150 #
SIZE : 25 MM TO 400 MM
RATING : 300 #
SIZE : 25 MM TO 400 MM

STRAINER

CAST CARBON STEEL

DESIGN : Y-TYPE (PN 40)
SIZE : 15 MM TO 250 MM

CAST STAINLESS STEEL

DESIGN : Y-TYPE (PN 40)
SIZE : 15 MM TO 300 MM

CAST IRON

DESIGN : Y-TYPE / POT TYPE /
T-TYPE (DIRT BOX)
ENDS : SCREWED / FLANGED
SIZE : 15 MM TO 300 MM



STAINLESS STEEL

DESIGN : Y-TYPE (150#)
ENDS : SCREWED /
SOCKET WELD
SIZE : 15 MM TO 80 MM

PULP VALVES

CAST IRON

OPERATION : MANUALLY / PNEUMATICALLY
ENDS : WAFER TYPE
SIZE : 40 MM TO 500 MM



GLOBE VALVE

BS 5352/BS 6755/BS 1873/
ASME B 16.34/DIN 3356/API 602/API 598

STAINLESS STEEL (BAR STOCK)

RATING : 150 / 300 #
SIZE : 8 MM TO 100 MM

FORGED CARBON STEEL

RATING : 800 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM
RATING : 150 / 300 #
SIZE : 15 MM TO 50 MM

FORGED STAINLESS STEEL

RATING : 800 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM
RATING : 150 #
SIZE : 15 MM TO 50 MM

CAST IRON

RATING : 125 / 150 #
SIZE : 25 MM TO 600 MM



CAST CARBON STEEL

RATING : 150 #
SIZE : 15 MM TO 300 MM
RATING : 300 #
SIZE : 15 MM TO 300 MM
RATING : 600 #
SIZE : 25 MM TO 200 MM
RATING : 900 #
SIZE : 50 MM TO 200 MM

CAST STAINLESS STEEL/ALLOY STEEL

RATING : 150 #
SIZE : 25 MM TO 400 MM
RATING : 300 #
SIZE : 25 MM TO 400 MM

DIN GLOBE VALVES

BS 5352/BS 6755/BS 1873/
ASME B 16.34/DIN 3356/API 598

CAST CARBON STEEL

RATING : PN 40 / PN 64
SIZE : 25 MM TO 300 MM

CAST STAINLESS STEEL/ALLOY STEEL

RATING : PN 40 / PN 64
SIZE : 25 MM TO 400 MM



CAST IRON

RATING : PN 10 / PN 16
SIZE : 15 MM TO 250 MM

FORGED BALL VALVES

FORGED CARBON STEEL

DESIGN : 3 PC
ENDS : SCREWED / SOCKET WELD
SIZE : 15 MM TO 50 MM

FORGED STAINLESS STEEL

DESIGN : 3 PC
ENDS : SCREWED / SOCKET WELD
SIZE : 15 MM TO 50 MM



NON RETURN VALVES (CHECK VALVES)

BS 5352/BS 6755
BS 1868/ASME B 16.34/API 6D/API 598

STAINLESS STEEL (BAR STOCK)

RATING : 150 / 300 #
SIZE : 8 MM TO 100 MM

FORGED CARBON STEEL

RATING : 800 # / 150 # / 300 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM

FORGED STAINLESS STEEL

RATING : 800 # / 150 #
SIZE : 15 MM TO 50 MM
RATING : 1500 #
SIZE : 15 MM TO 40 MM

CAST IRON

RATING : 125 / 150 #
SIZE : 25 MM TO 400 MM



CAST CARBON STEEL

RATING : 150 #
SIZE : 25 MM TO 600 MM
RATING : 300 #
SIZE : 25 MM TO 450 MM
RATING : 600 #
SIZE : 40 MM TO 300 MM
RATING : 900 #
SIZE : 50 MM TO 200 MM

CAST STAINLESS STEEL/ALLOY STEEL

RATING : 150 # / 300 #
SIZE : 25 MM TO 400 MM

DIN NON RETURN VALVES

BS 5352/BS 6755/BS 1873/BS 1868/
ASME B 16.34/DIN 3356/API 598

CAST CARBON STEEL

RATING : PN 40
SIZE : 15 MM TO 300 MM
RATING : PN 64
SIZE : 15 MM TO 300 MM

CAST STAINLESS STEEL/ALLOY STEEL

RATING : PN 40
SIZE : 15 MM TO 250 MM

CAST IRON

RATING : PN 10 / PN 16
SIZE : 15 MM TO 250 MM



KNIFE GATE VALVES

CAST CARBON STEEL

RATING : 150 #
ENDS : FLANGED / LUGGED TYPE
SIZE : 50 MM TO 600 MM

STAINLESS STEEL

RATING : 150 #
ENDS : FLANGED / LUGGED TYPE
SIZE : 50 MM TO 600 MM

CAST IRON

RATING : 150 #
ENDS : FLANGED / LUGGED TYPE
SIZE : 50 MM TO 600 MM



BUTTERFLY VALVES MODEL NO. F-7,8,9

API 609 / BS 5155 / IS 13095
MSS SP-67

CAST IRON

OPERATION : LEVER / GEAR / ACTUATOR
DESIGN : CENTRIC / OFFSET DISC
SEAT TYPE : INTEGRALLY MOULDED / REPLACEABLE
ENDS : WAFER TYPE / DOUBLE FLANGED / LUGGED TYPE
SIZE : 40 MM TO 1200 MM



CAST CARBON STEEL

OPERATION : LEVER / GEAR / ACTUATOR
DESIGN : CENTRIC / OFFSET DISC
SEAT TYPE : INTEGRALLY MOULDED / REPLACEABLE
ENDS : WAFER TYPE / DOUBLE FLANGED / LUGGED TYPE
SIZE : 40 MM TO 1200 MM

STAINLESS STEEL

DESIGN : CENTRIC / OFFSET DISC
OPERATION : LEVER/GEAR/ACTUATOR
ENDS : WAFER / LUGGED TYPE
SIZE : 40 MM TO 300 MM

BALL VALVES

CAST IRON

DESIGN : 1 PC / 3 PC
ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 15 MM TO 200 MM



CARBON STEEL

ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 15 MM TO 100 MM

CAST CARBON STEEL

ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 15 MM TO 400 MM

STAINLESS STEEL

MOC : SS304 / SS316 (BAR STOCK)
DESIGN : 1 PC / 2PC / 3PC
ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 15 MM TO 250 MM

DESIGN : 1 PC / 2PC / 3PC
ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 6 MM TO 100 MM

INVESTMENT CASTING BALL VALVES

MOC : CF8 / CF8M / CF3 / CF3M
DESIGN : 1 PC / 2PC / 3PC
ENDS : SCREWED / SOCKET WELD / FLANGED



MOC : WCB
DESIGN : 1 PC / 2PC / 3PC
ENDS : SCREWED / SOCKET WELD / FLANGED
SIZE : 6 MM TO 200 MM

DIAPHRAGM VALVES

CAST IRON

LINING : NATURAL RUBBER / EBONITE / NEOPRENE / NITRILE
SIZE : 15 MM TO 350MM



ALSO AVAILABLE

- Safety Valves
- Relux Valves
- Flange Fittings
- Tube / Sight Glass
- Plug Valves
- Pinch Valves
- CI / DI Fittings
- Needle Valves
- Sluice Valves
- Foot Valves
- Rotary Joints
- Hydraulic Test Pumps

CERTIFICATION AND APPROVAL.



WAFER TYPE CHECK VALVES

CARBON STEEL

SIZE : 25 MM TO 600 MM
ENDS : WAFER TYPE



STAINLESS STEEL

SIZE : 25 MM TO 600 MM
ENDS : WAFER TYPE

INVESTMENT CASTING STEAM TRAP

STAINLESS STEEL

ENDS : SCREWED/SOCKET WELD
SIZE : 15 MM TO 25 MM



BEENA

Manu

PL

A

CONTA



ORKS

rial Valves.

27177

