



 **OPTITECH**®

An EN ISO 13485:2016 COMPANY



Millisecond Focusing



SLIT LAMP | MODEL : iS3

- **Parallel Type, Galilean System, 3 Step Changer**
Superior optic quality, provides stereoscopic and comfortable view with broad beam, wide field and high depth of field
- **Warm LED Illumination , Better Conformity , Longer Life Time**
Works 50 thousand hours, and suitable for human tissue
- **Precision Machining makes Smooth and Flexible Movement**
- **Brightness Control Continuously**
- **Interface for laser and applanation tonometer reserved**
- **3 Step**



SLIT LAMP | MODEL : iS7 / DIGITAL WDR

- **iS7, Slit Lamp Microscope | 5 Step New Optics with inbuilt Yellow Filter | LED.**
- **iS7, Digital, Slit Lamp Microscope | 5 Step New Optics with inbuilt Yellow Filter | LED | Digital System with Software.**
- **iS7, Digital (WDR), Slit Lamp Microscope | 5 Step New Optics with inbuilt Yellow Filter | LED | Digital System with infrared function for meibomian glands examination.**
- **Optional : Dry Eye Assessment Device**



SLIT LAMP PORTABLE | MODEL : HL9

- Lightweight, Single hand operate.
- Linkable Eyepieces, 2 Step Changer.
- Ideal for Paediatrics, Veterinary Surgeon, Nursing Home, Carry-out, Private Ophthalmologist.
- Packed in Alu-Alloy carrying case.



SLIT LAMP | MODEL : ALPHA / ALPHA-125

- Stereo Microscope 2 Step
- Working Distance- 100 mm
- Objective Lens Focal Length- 1X, 1.6X
- Eye Pieces (Large Optics)- 10X
- Total Magnification - 10X, 16X (Two Step)
- Inter Pupillary Distance- 55-75 mm
- Diopter Adjustment Range-6D to +6D



PERIMETER | MODEL : VF 1000

- Standard Goldmann White-on-White Perimeter.
- LED Light Source
- Auto eye recognition and pupil diameter measurement.
- Human design of mechanical and structure.
- Voice prompts and instruction.
- Data operation for patient information uploading and downloading.



FUNDUS CAMERA | MODEL : FC161

- Auto Split Focusing Technology Millisecond Focusing Speed.
- 5 Advantages : High Resolution, Non-Mydriatic, 9 Fixation Targets, Smart Touch Operation, Real time Uploading



CORNEAL TOPOGRAPHY SYSTEM & DRY EYE ANALYZER | MODEL: DEA 520

- Corneal Topographer DEA 520
- The Ocular Diagnostic Master integrated dry eye & corneal topography analysis.



NEITZ
Made by Neitz for Your Medical Field

Medical Instruments / Peripheral Instruments



**OPERATION TABLE CUM TREATMENT CHAIR
MODEL : OT T CLASSIC**

- Height Range Min / Max : 630mm (25") / 840mm (33")
- Lifting Speed : 8mm/s
- Maximum Load Capacity : 250 Kg
- Sleeping Bed Tilting : 30 Degree
- Bed Length : 1830mm (72")
- Bed Width : 610mm (24")
- Base Size : 840mm (34") / 560mm (22")
- Power Supply : AC 230V / 110V 50/60 Hz
- Chair Position to Table & Vice-versa : Motorized
- Gross Weight : 120 Kgs



PHACO TROLLEY | MODEL : PHACO-15

- Adjustable Instrument Trolley (PHACO Machine) with a hand lever that enables tray positioning in any height in the range of 800 to 1196mm.
- Adjustable ABS tray for placing surgical instruments.
- The tray is removable from the stand to facilitate complete sterilization.
- Tray is affixed to a stainless steel IV pole whose height can be adjusted.
- The surgical equipment platform can be custom made for any requisite measurement and has anti-skid surface.
- Twin castor wheels with direction locking and heavy load bearing capacity.



MOTORISED SURGEON CHAIR | MODEL : SC 801

- Weight Base Unit : 43 Kg / 95 lbs
- Length (Chasis) : 560 mm
- Width (Chasis) : 560 mm
- Electric : Battery operated – Charger 100 – 240 V
- Cushions : Black, Blue and Green colour as per standards – other colours as per options

CONTACT US