



- A - Operation & Maintenance Contracts Man Power Supply.
- B - Annual Service Agreements with spares / without spares
- C - Call / Visit Based Services.
- D - All Types of Spare Parts.
- E - Contract Packaging inclusive all packaging related products.
- F - All types of Packaging Machinery Repair & Services.
- G - Any make of Packaging Machines.



ABOUT US :

We work hard for you, so that your machine always up.

Unique packaging and automation is running by professionals and supplying a wide range of packaging, tapping and sealing machine for both small and large industries.

We have earned an excellent reputation for our competitive prices, product knowledge and customer service.

Unique packaging commits to our customers that we are always provide free advise/information about all types of strapping and packaging products and online service supports by e-mail with telephonic.

Unique packaging can provide spare parts of all types/made strapping, taping, sealing machine.

SERVICES :

We make tailor made offers as suitable to customer for service contact and new machine .

At UPA our standard hours for service and aftercare support are 24*7 in a week. We also provide complementary technical support service during our standard hours which allows service contract holders to obtain advice and support through a telephone consultation with one of our skilled engineers. We are able to service and repair on most makes of strapping machinery. We cover most of the India or can offer a return to base repair service where we can provide an estimate for repairs prior to any work being carried out.



- Annual Service Agreements
- Comprehensive Service Contracts
- Call / Visit Based Services
- Operation & Maintenance Contracts
- Spare Parts

Factory certified repair technicians guarantee the best repair possible!

Support makes all the difference and the UPA dedicated service team is just a phone call away. Our trained technicians are available for on-site service calls as well as expedited same day service for situations that require immediate action. UPA service technicians, service all major brands packaging equipment systems and packaging equipment solutions. The following are some of our main packaging equipment repair solution services.

Power Stretch Wrapping Machine Repair

Our technicians support, service and repair a full range of pallet wrapper system types such as turntable, rotary arm, straddle, pallet wrapper with scale, mobile pallet wrapper, fully automatic and semi-automatic stretch wrappers.

Shrink Wrapping Machine Repair

Does your Shrink wrap machine need repair or support services. We have factory trained technicians that provide on-site service calls as well as same day dispatch service for situations that require immediate action. Repair shrink wrap machines and shrink packaging systems such as fully and semi-automatic sleeve wrappers.

Battery Operated / Pneumatic Strapping Tool Repair

At the UPA Service Centre, we take service seriously. UPA has gained a reputation as a quality repairing for most major brands of Strapping/Packaging tooling and machines. One of a few companies in the India who is able to repair strapping tools and machines of all types; pneumatic, electric, battery operated and manual.

Automatic Strapping Machine Repair & Service

We are able to service and repair on most makes of strapping machinery such as Strapex, ITW, Pack way and Trans pack. We stock a variety of parts for your Strapping equipment. Let UPA trained service technicians assist you with troubleshooting, parts selection and ordering to help insure you order the correct replacement parts for your equipment.

PRODUCTS :

Semi-Automatic Strapping Machine



SPECIFICATION

POWER SUPPLY	: AC 220V (50/60hz)- 0.4KW
STRAP WIDTH	: 6MM TO 15MM(ADJUSTABLE)
ELE. MOTOR	: ¼ hp, , 1440 rpm, 220vac- 200W
Straping Speed	: 2.0sec. /per strap
Sealing method	: heat sealing
Dimension	: 910mm(L)*580mm(w)*750mm(H)
Net Weight	: 100KG
Package Dimensions	: min. 60mm to 60mm (L*W)

STRAPPING MACHINE



Top	: Powerised Rollers for heaving products movements.
Box weight	: Weight 5 to 70 kg
Box Min. Sizes	: Height 30mm to as arch sizes. Width: - 350mm to arch sizes

AUTOMATIC STRAPING LINE



ALUMINIUM ARCH FULLY AUTOMATIC STRAPPING LINE

Features :

- Easy operation
- Easy maintenance
- Convenient to adjust strapping tension:
- 60 sec. auto-stop: electricity-saving
- Advanced P.C.B control system
- Made in Taiwan: Quality assurance
- Super-light strapping tension

Optional:-

- Ball table top for easily 360 degree movements of heavy weight products.
- Side sealing strapping machine : Oil Industries.
- Low height strapping machine :- for heavy weight Industry - (Textile and Corrugated Industry)

SPECIFICATION

STRAP WIDTH	: 9,12,15 (As per need)
STRAPPING TENSION	: 0-80 KGS
STRAPPING SPEED	: 2.4SEC/STRAP (12 STRAP/MIN)
ARCH SIZE	: W850*H600MM
POWER	: 3PHASE, 440VAC,

- New modular aluminium Single piece arch for easy strap movements.
- Hinged table top for easily feeding the strap.
- Instant heating system.
- Available for both PP and PET strap (kindly confirm at the time of order)
- Easily loading and unloading strap rolls.
- We can make many straps on each boxes as per requirement's (kindly confirm at the time of order).
- We can adjust position of straps by moving/ locations shifting sensors.
- Every time we can get strap on same locations.
- Operators free machine – required only for loading and unloading strap rolls.



MS ARCH FULLY AUTOMATIC STRAPPING LINE

Pallet Strapping Machine



Power Supply	220V/110V/ 1-Phase
Power	0.66 KW
Max. Strapping Force	60 Kg
Strap Width	6-15 mm
Min. Strapping article	60 mm
Strapping speed	1.5 sec./ per strap
External Dimensions (L x W x H)	945 x 690 x 1140
Weight	100 Kg

Automatic Tapping Machine



Model	S3-6050 (3Inch)	S34038(2Inch)
Dimensions	1755x800 (960 1650)	1730x950x (960/650)
Max. Size	500x600	500x600
Min. Size	140x110	100x100
Tapping Speed	20 (m/min)	
Height of Table	635-780	508-780
Width of Adh. Tap	48/76	48
Voltage (V/Hz)	AC 200/50	
Weight (Kg)	120 Kg	115 Kg

Polyester Strap



Advantage

- Lower cost and environmental friendly as well
- Best suitable for medium to heavy application.
- Rust free and safe working.
- High heat-resisting and lower elongation rate.

Specification

- Economy.
- Corrosion Free.
- Impact Resistance.

Polypropylene Strap

Polypropylene strap (oriented or tensilized) is an economical material designed for light to medium duty unitizing, palletizing and bundling. It is available in various widths, thicknesses, and polymer variations (e.g., copolymers).



Types : Semi Automatic & Fully Automatic
Size : 9mm ~ 15mm

Advantage

Lower cost and environmental friendly as well
Best suitable for medium to heavy application.
Rust free and safe working.
High heat-resisting and lower elongation rate

Power Stretch Wrapping Machine



Features and benefits

- Heavy duty steel structure with box type column.
- AC Drives and Motors - Reduced maintenance and better performance
- UPA - Powered pre-stretch, variable up 200 to 450% (Optional)
- Automatic pallet height sensor.
- 2.6 Mtr. wrapping height suitable for high cube container
- PLC Controlled with digital display of stretch % and weight of the film consumed per pallet.
- Reinforcement wrap function - for desired no of wraps at any given height of the pallet.

Stretch Film



Stretch wrap or stretch film is a highly stretchable plastic film that is wrapped around items. The elastic recovery keeps the items tightly bound. In contrast, shrink wrap is applied loosely around an item and shrinks tightly with heat. It is frequently used to unitize pallet loads but also may be used for bundling smaller items. Types of stretch film include bundling stretch film, hand stretch film, extended cor stretch film, machine stretch film and static dissipative film.

Bopp Adhesive Tape



Bioaxially Oriented Polypropylene (BOPP) Film coated with acrylic based adhesive in different micron (gsm) coating thickness. The BOPP tape is available in different colours. BOPP tape is used in carton box sealing and for stationary purpose. Printing of single and multiple colour is also possible with logo or customized design.

Strapping Tool : Battery Operated Strapping Tools



P328

Strap tension: (adjustable)

Strap qualities:
Polyester (PET)

Strap dimensions:
12.0 – 16.0 x 0.40 – 1.05 mm
7/16 – 5/8 x .016 – .041"

Plastic Strapping Tools: In addition to the conventional systems for steel strapping, FROMM has developed equipment for polyester strapping. This new type of strapping is flexible, absorbing shock impact during shipping, loading and unloading more effectively than steel strapping.

The range is divided in pneumatic, manual and electric tools. Electric tools allow an independent working range, ideal for applications requesting not only flexible handling of the tool but also high tension of the strapping

Battery Operated Strapping Tools UPA-160

The ORT 200 is a new generation of battery powered hand strapping tool. Strapping has never been so easy. The 200 is suitable for PP and PET strapping. Its features include one-piece strap insertion, one hand operation for tensioning and sealing.

Details

Strap Width - 2-16 mm Adj
Strap Thickness - Polypropylene 0.6 - 1.0 mm
Weight - 3.9 KG
Size- 375 X W 130 X H 140 mm
Tensioning - Electrically (pushbutton) 400 - 2000N
Sealing - Electrically (pushbutton) Friction weld Seal
Battery - 100-200 Strappings with one battery Charge



Pneumatic tools for plastic strapping

Strap Qualities :
Polyester (PET)

Strap dimensions :
10.0 – 16.0 x 0.40 – 1.05 mm
3/8 – 5/8 x .016 – .041"

Strap Tension :
400 – 2100 N (Adjustable)



SEALLESS STEEL STRAPPING TOOLS (Regular duty)



Technical characteristics:

Width of steel strapping: 1/2", 5/8", 3/4" (13, 16, 19 mm)

Thickness of steel strap:

– Regular duty (< 850 N/sq.mm): up to 0.025" (0.64 mm)

Strapping tape tension force, N: 6 000

Weight: 8.5 lbs (3.8kg)

Overall dimensions, mm: 390 x 105 x 185

Tensioner

Technical characteristics

Type of joining the strap:

Weight: 8.5 lbs (3.8 kg)

Tension: 4500-8400 N

Overall dimensions, mm: 610 126 70

Steel strap width: 1" (25mm), 1 1/4" (32mm)

Steel strap thickness: up to 0.044" (1.1 mm)



Sealing tool



Width of used steel strap: 1 1/4" (32mm)

Quantity of notches: 1 pair

Thickness of strap (< 850 N/sq.mm): up to 0.044" (1.1 mm)

Weight: 6.17 lbs (2.8kg)

Overall dimensions, mm: 670 120 40

Continuous Sealer



CS 3 H



Csi 3 HVP



CS 75V



To seal different types of pre filled flexible bags continuously. Applications in various industries like food processing, chemicals engineering—

Features

- Adjustable temperature /micro controller models suitable for a wide spectrum of materials | Variable speed conveyor | Vertical / Horizontal mountable models
- H- Horizontal model | HV- Convertible into horizontal or vertical | V- Vertical model CS- Continuous sealer (suitable for laminates) | CSI- Intelligent micro-controller based sealer (suitable for wide spectrum of materials)

Technical Specifications

Model	Sealing Width (mm)	Max Load	Power	Speed (M/Min)
CS 3 H/ HV	12	3 Kg	240V	0-12
Csi 3 HP/ HVP	12	3 Kg	240V	0-12
Csi 15HVP	12	15 Kg	240V	0-10
CSI 30V	12	30 Kg	240V	0-10
CS 75V	12	75 Kg	240V	0-10

Paste/ Liquid Filler



Semi Automatic Paste filling Machine GCG-BL

Semi Automatic Filling machine for filling thick fluids and pastes.

Features:

- Pneumatically activated piston with step less adjustment for volume | Simple and compact structure | SS construction, easy to wash | Filling volumes 100 ml ~ 1000 ml | Outlet nozzle equipped with valve to avoid dripping | SS storage hopper
- Manual and auto modes | Speed: 10 ~ 15 dozes / min
- Accuracy - + / - 1 %



Gravimetric Weigh Dispenser GW 10



Gravimetric weigh dispenser GW 10 is an ideal machine for automatically dispensing preset weights of free flowing products like tea dust, sugar, rice, baked rice powder, dal, seeds etc. This is a load cell based pneumatically operated machine. It has a storage hopper and is equipped with coarse feed and fine feed system to maintain the weighing accuracy. The output could be collected in a bag directly which can be sealed on a sealing machine.

Technical Specifications

Input power	: 240V 50Hz
Weighing/dispersing range	: 200gms ~ 1000gms 500gms ~ 2000gms/ 1Kg to 5Kg/ 5Kg ~ 10Kg
Accuracy	: +/- 0.5%
Speed	: < /=4sec/dispense (depending on weight & material)
Compressed air supply	: 6 ~ 10 bar

Approved by legal metrology department





Gas Filling



Hand Sealer



Band Sealer



Mobile Sealing



Induction Sealing



Hand Sealing Machine



Pedal Machine



Tape Dispenser



Induction Sealer



Hand Wrapper



Stretch Wrapping



Box Strapping Machine



Automatic Box Strapping Machine



Carbon Sealer



Steel Strapping Sealer



Steel Strapping Tensioner



Battery Tool Fromm



Battery Tool Fromm



Battery Tool UPA-100



Pneumatically Pet Strapping Tool



Pneumatically Pet Strapping Tool

*In our continuous process of product improvement, specifications mentioned herein are subject to change without prior notice.

OUR CHANNEL PARTNER



Major Clients



Unique Packaging And Automation

Providing Good Quality of Services Through Good Quality of Products

Pooja Electronics, Mahadev
Colony, Panipat, Haryana
Mob.: +91-9215521314

Opposite - VVA Developer
Near Power Grid
Bhiwadi-Alwar Road (raj.)
Mob.: +91-9991226074

E-mail : uniquepackagingandautomation@gmail.com, info@unipackauto.com
www.unipackauto.com

Sales department :- +91-8739950100, +91-8740850100

E-mail :- sales@unipackauto.com

BRANCHES :

Bhiwadi (Rajasthan)
07232001235

Panipat (Haryana)
09215521314

Bhajanpura (Delhi)
09717341089