





Engine

Type: 4 Stroke, Single Cylinder Liquid cooled, SI Engine

• **Displacement:** 225.8 cc

• **Maximum Power :**7.3 kW @ 5000 rpm

• **Maximum Torque:**17.5 Nm @ 3000 rpm

• Bore x Stroke: 66 mm x 66 mm

• Starting: Electric & Hand Start

• Ignition: High Energy Inductive Ignition DC TCI

- Fuel feed system: Side Draft Carburetor with Intake and Exhaust controlled by Valve Mechanism
- **Lubrication**: Positive Displacement type oil pump mounted on an oil sump





Transmission, Chassis, Suspension

- **Transmission:** 4 Forward and 1 Reverse speed, constant mesh, Fork & Cam type shift mechanism
- Type:Semi Monocoque
- Front & Rear: Trailing arm type, constant rate coil spring with co axial hydraulic damper





Breakes, Wheels & Tyres

- Front & Rear : Drum, Hydraulic
- Rim size Front & Rear :3.00D x 8
- **Tyre size Front & Rear:** 4.00 8, 6 PR





Electricals

• **Battery:**12V, 32 Ah

• **Head lamp:** 35/35W, DC

• Tail lamp, Stop lamp: 21 W, 5W

• Turn signal lamp:10 W

• Reverse lamp: 21 W

• Warning lamp: Low oil, Low fuel





Dimensions, Weights, Capacity & Gradeability

• Wheelbase:1990 mm

• Wheel track: 1150 mm

• Overall length: 2647 mm

• Overall Width: 1329 mm

• Overall Height: 1740 mm

• Kerb weight : 373 kg

• Ground clearance: 165 mm

• **Fuel tank capacity :** LPG – 20.6 litrs. Water Equivalent, Petrol – 3 ltrs.

Gradeability 12 degrees

CALL US ON

• Ph: -+91 9372703792

• Ph: -+91 9029062626

• Whatsapp no +91 9372703792

• email Id: exports@syndicateoverseas.net