

TPR 350-04 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 350 bar 35 Mpa
5075 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060303004

TPR 350-03 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 350 bar , 35 Mpa ,
5075 psi

RATED TEMPERATURE:- 100 °C , 212 °F

PART NO :- 4060303002

TPR 255-03 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 255 bar 25,5 Mpa ,
3700 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060204002

TPR 255-04 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 255 bar 25,5 Mpa ,
3700 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060204004

TPR 255-05 ROTATING NOZZLE :-

UGELLO CERAMICA
CERAMIC NOZZLE



PERMISSIBLE PRESSURE :- 255 bar 25,5 Mpa
3700 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060204006

TPR 400-03 ROTATING NOZZLE :-

UGELLO CERAMICA
CERAMIC NOZZLE



PERMISSIBLE PRESSURE :- 400 bar , 40 Mpa ,
5800 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060401002

TPR 400-04 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 400 bar, 40 Mpa ,
5800 psi

RATED TEMPERATURE :- 100 °C , 212 °F

PART NO :- 4060401004

ROTOJET 400-03 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 400 bar , 40 Mpa ,
5800 psi

RATED TEMPERATURE :- 90 °C , 200 °F

PART NO :- 204006900

ROTOJET 400-04 ROTATING NOZZLE :-

UGELLO CERAMICA
CERAMIC NOZZLE



PERMISSIBLE PRESSURE :- 400 bar , 40 Mpa ,
5800 psi

RATED TEMPERATURE :- 90 °C , 200 °F

PART NO :- 204006910

ROTOJET 400-05 ROTATING NOZZLE :-

UGELLO CERAMICA
CERAMIC NOZZLE



PERMISSIBLE PRESSURE :- 400 bar , 40 Mpa
5800 psi

RATED TEMPERATURE :- 90 °C , 200 °F

PART NO :- 204006920

ROTOJET 400-06 ROTATING NOZZLE :-



PERMISSIBLE PRESSURE :- 400 bar, 40 Mpa ,
5800 psi

RATED TEMPERATURE :- 90 °C , 200 °F

PART NO :- 204006930

SVL 50 SAFETY VALVE :-



PERMISSIBLE PRESSURE :- 560 bar 56 Mpa
8100 psi

RATED FLOW :- 100 l/min 26,4 USGpm

RATED TEMPERATURE :- 90 °C 194 °F

SVT 40 SAFETY RELIEF VALVE :-



RATED PRESSURE:- 360 bar 36 Mpa
5220 psi

PERMISSIBLE PRESSURE :- 400 bar 40 Mpa
5800 psi

MINIMUM ADJUSTABLE PRESSURE :- 36 bar
3.6 Mpa
522 psi

RATED FLOW :- 25 l/min 6.6 USGpm

RATED TEMPERATURE :- 90 °C 194 °F

TS-33 03 SAND BLAST NOZZLE 250 BAR:-



RATED PRESSURE :- 220Bar, 22 Mpa 3200 psi

PERMISSIBLE PRESSURE :- 250Bar, 25Mpa,
3625 Psi

RATED TEMPERATURE :- 90°c 194°F

HOSE BARB:- 13mm 05,11 in

PROBE LENGHT:- 500mm 19,7in

PART NO :- 4053200002

TPS-560 SAND BLAST NOZZLE 500 BAR :-



RATED PRESSURE :- 500 Bar, 50 Mpa
7250 psi

PERMISSIBLE PRESSURE :- 560Bar, 65 Mpa,
8100 Psi

RATED TEMPERATURE :- 90°C 194°F

RATED FLOW:- 80 l/Min 21 USGpm

PART NO :- 470018

MV 925 F TRIGGER GUN :-



RATED PRESSURE :- 280 bar 28 Mpa

4060 psi

PERMISSIBLE PRESSURE :- 310 bar 31 Mpa

4500 psi

RATED FLOW :- 30 l/min 8 USGpm

RATED TEMPERATURE :- 160 °C 320 °F

PART NO :- 4012205000

MV 925 M TRIGGER GUN :-



RATED PRESSURE :- 280 bar 28 Mpa

4060 psi

PERMISSIBLE PRESSURE :- 310 bar 31 Mpa

4500 psi

RATED FLOW :- 30 l/min 8 USGpm

RATED TEMPERATURE :- 160 °C 320 °F

PART NO :- 4012205003

ML 955 F TRIGGER GUN :-



RATED PRESSURE :- 360 bar 36 Mpa
5220 psi

PERMISSIBLE PRESSURE :- 400 bar 40 Mpa
5800 psi

RATED FLOW :- 40 l/min 10,6 USGpm

RATED TEMPERATURE :- 160 °C 320 °F

PART NO :- 4017000006

ML 955 M TRIGGER GUN :-



RATED PRESSURE :- 360 bar 36 Mpa
5220 psi

PERMISSIBLE PRESSURE :- 400 bar 40 Mpa
5800 psi

RATED FLOW :- 40 l/min 10,6 USGpm

RATED TEMPERATURE :- 160 °C 320 °F

PART NO :- 4017000008

ML 510 TRIGGER GUN :-



RATED PRESSURE :- 500 bar 50 Mpa
7250 psi
PERMISSIBLE PRESSURE :- 560 bar 56 Mpa
8100 psi
RATED FLOW :- 60 l/min 16 USGpm
RATED TEMPERATURE :- 120 °C 250 °F
PART NO :- 4013300000

MV 925 KARCHER FITTING :-



RATED PRESSURE :- 280 bar 28 Mpa
4060 psi
PERMISSIBLE PRESSURE :- 310 bar 31 Mpa
4500 psi
RATED FLOW :- 30 l/min 8 USGpm
RATED TEMPERATURE :- 160 °C 320 °F
PART NO :- 4012205006

VAN NOZZLE IDROJET 2...035 :-



RATED PRESSURE :- 207 bar 20,7 Mpa

3000 psi

PERMISSIBLE PRESSURE :- 220 bar 22 Mpa

3200 psi

RATED FLOW :- 30 l/min 8 USGpm

RATED TEMPERATURE :- 150 °C 300 °F

PART NO:- 204008010

VHP 51 UNLOADER VALVE 500 BAR :-



RATED FLOW :- 100 l/min 26,4 USGpm

RATED TEMPERATURE :- 90 °C 194 °F

RATED PRESSURE :- 500 bar 50 Mpa

7250 psi

PERMISSIBLE PRESSURE :- 550 bar 55 Mpa

8000 psi

SPRING COLOUR :- Grey

PART NO :- 4072000122

GREY VRT 3 UNLOADER VALVE :-



RATED FLOW :- 40 l/min 10.5 USGpm

RATED TEMPERATURE :- 90 °C 194 °F

RATED PRESSURE :- 280 bar 28 Mpa
4060 psi

PERMISSIBLE PRESSURE :- 310 bar 31 Mpa
4500 psi

SPRING COLOUR :- Black

PART NO :- 4072000000

VHP 39 UNLOADER VALVE :-



RATED FLOW :- 40 l/min 10,5 USGpm

RATED TEMPERATURE :- 90 °C 194 °F

RATED PRESSURE :- 350 bar 35 Mpa
5070 psi

PERMISSIBLE PRESSURE :- 390 bar 39 Mpa
5650 psi

SPRING COLOUR :- Black

PART NO :- 4072000026

VRT 100 UNLOADER VALVE 350 BAR 100 LPM :-



RATED FLOW :- 100 l/min 26,4 USGpm
RATED TEMPERATURE :- 90 °C 194 °F
RATED PRESSURE :- 170 bar 17 Mpa 2465 psi
PERMISSIBLE PRESSURE :- 190 bar 19 Mpa 2760 psi
RATED PRESSURE :- 320 bar 32 Mpa 4640 psi
PERMISSIBLE PRESSURE :- 350 bar 35 Mpa 5075 psi
SPRING COLOUR :- Yellow , Blue
PART NO :- 4072000033

VHP 31/250 170 BAR 250 LPM :-



RATED FLOW :- 250 l/min 66 USGpm
RATED TEMPERATURE :- 90 °C 194 °F
RATED PRESSURE :- 150 bar 15 Mpa 2175 psi
PERMISSIBLE PRESSURE :- 170 bar 17 Mpa 2465 psi
RATED PRESSURE :- 280 bar 28 Mpa 4060 psi
PERMISSIBLE PRESSURE :- 310 bar 31 Mpa 4500 psi
SPRING COLOUR :- Grey , Black-Grey
PART NO :- 4072000094

VHP 31/250 310 BAR 250 LPM :-



RATED FLOW :- 250 l/min 66 USGpm
RATED TEMPERATURE :- 90 °C 194 °F
RATED PRESSURE :- 150 bar 15 Mpa 2175 psi
PERMISSIBLE PRESSURE :- 170 bar 17 Mpa 2465 psi
RATED PRESSURE :- 280 bar 28 Mpa 4060 psi
PERMISSIBLE PRESSURE :- 310 bar 31 Mpa 4500 psi
SPRING COLOUR :- Grey , Black-Grey
PART NO :- 4072000095

VHP 18/160 160 BAR 160 LPM :-



RATED FLOW :- 160 l/min 42,3 USGpm
RATED TEMPERATURE :- 90 °C 194 °F
RATED PRESSURE :- 160 bar 16 Mpa
2320 psi
PERMISSIBLE PRESSURE :- 180 bar 18 Mpa
2610 psi
SPRING COLOUR :- Grey
PART NO :- 4072000114