

Laboz Ing

Deep Freezer Ultra low Temp -20°C(Horizontal) LI-0074

Double walled construction. Inner chamber made of S.S and outer M.S powder coated. A water drain cock and S.S tray is provided at a base of the chamber. Temperature can be controlled up to -20°C by electronic digital temperature controller cum indicator . PUF insulation is provided between the walls to achieve set temperature in short time .A sealed compressor with all the accessories and fan cooled condenser are fitted at the bottom below the working chamber. To work on 220/230 V ,Ac , Single Phase supply.



Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.

Deep Freezer Ultra low Temp -40°C(Horizontal) LI-0075

Same As above model.

Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.

Deep Freezer Ultra low Temp -86°C(Horizontal) LI-0076

Same As above model.

Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.



Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-

201102, www.labozinc.com, labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozinc.com, labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozinc.com, labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozinc.com, labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozincsales@gmail.cominfo@labozinc.com, 8860356096, 9136440369120, www.labozincsales@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.cominfo@gmail.



Laboz Ing

Deep Freezer Ultra low Temp -20°C(Vertical) LI-0077

Double walled construction . Inner chamber made of S.S and outer M.S powder coated . A water drain cock and S.S tray is provided at a base of the chamber. Temperature can be controlled up to -40°C by electronic digital temperature controller cum indicator . PUF insulation is provided between the walls to achieve set temperature in short time .A sealed compressor with all the accessories and fan cooled condenser are fitted at the bottom below the working chamber. To work on 220/230 V ,Ac , Single Phase supply.

Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.



Deep Freezer Ultra low Temp -40°C(Vertical) LI-0078

Same As above model

Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.





Deep Freezer Ultra low Temp -86°C(Vertical) LI-0079

Same As above model

Capacity:

4.1 Cu ft.

6.0 Cu ft.

10.0 Cu ft.

12.0 Cu ft.



Blood Bank refrigerator LI-0060

Double walled construction . Inner chamber made of S.S and outer M.S powder coated . S.S tray to hold blood bags with separate acrylic doors for each compartment. Temperature can be controlled up to 0° C by electronic digital temperature controller cum indicator with an accuracy of +/- 0.5 °C. A sealed compressor with all accessories and fan cooled condenser are fitted at the bottom below working chamber . inside temperature uniformity is maintained by air circulating fans. Suitable to work on 220/230 V Single Phase AC supply.

Capacity:

85 Lits (50 blood bags)

165 Lits (100 blood bags)

200 Lits (200 blood bags)

280 Lits (250 blood bags)

400 Lits (350 blood bags)

Optional accessories:

- Weekly temperature recorder
- Stablizer(3,4KVA)



Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-



Laboz Inc

Lypholizer (Freeze Dryer)-40°C LI-0097

Castor mounted steel frame with full accessories cabinet.

Complete with heavily insulated cooling coils made of copper for maximum efficiency. Temperature controlled by digital temperature controllercum indicator upto -40°C .A sealed compressor with all accessories and fan cooled condenser are fitted at the bottom below working chamber. Condensor trap is provided at non magnetic stainless steel dished bottom for complete effluent removal. Vacuum drum having 22.8 cm dia height is made up of non-magnetic stainless steel with Perspex top cover and incorporates 8/12 quick seal valves /ports for manifold drying . double stage vacuum pumps with gas blast vacuum of 1x10³ torr on pump head . sample port having 12.5 mm outer dia .provided for quick drying .Outer structure made of steel gives elegant and pleasant look .Suitable to work on 220/230 V AC Supply.



Capacity:

02 Lits 05 Lits

Optional accessories:

- Secondry drying unit.
- Pre- freezing Glycol Bath having temp upto-30°C
- Automatic Voltage Stablizer.

ICE FLAKE MACHINE Model: LI-Series

The ice flaking machine is complete with S.S body.cost inclusive. The unit is fitted with fully safety devices like Low water cut off, over load bins cost inclusive. Bin made by: S. S. SHEET Cabinet made by: S. S. SHEET WITH LINING Compressor: CFC FREE,RefrigerantR134a Condenser unit: AIR COOLED.LI Series Flake Ice Machine highly efficient..The machine will be running smoothly, hard to break and obviously it is very low maintenance as well. The indication can be showed on the PC board if there something goes wrong and the machine will be turned off itself and the instruction warning lights will be on. Such as:



Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-

201102,www.labozinc.com,labozincsales@gmail.cominfo@labozinc.com,8860356096,9136440369

Accessories: Bin Storage 30 Kgs (Inclusive)

Positive charge non return device for water circulation in decontaminated form(Inclusive)

Inlet water connection line for inlet & outlet coupling.(Inclusive)

Outlet water pipe with connector

Mortuary Cabinet & Freezer LI-0101

The unit is designed for storing the cadaverous under cool condition to prevent bodies from decomposition. Double walled construction with inner chamber made of S.S and outer made of M.S powder coated / S.S . Polyurethane PUF insulation is fitted between walls and whole structure is made on heavy duty iron angle frame mounted on castor for easy movality.

Single Body Double Body Four Body.



We can customize the unit as per requirement on special orders.