



Laboz Inc

LABOZ DENTAL CHAIR SPECIFICATIONS

Model : TEJAS

Electrically operated Luxury dental chair with 2 fixed programs Zero and working position.
3 side Chair controls Feather touch Hand, Assistant Panel & Foot control.
Multifunction Foot control, Adjustable Headrest.
Seamless seat upholstery with PU molded foldable armrest.
Timer controlled auto water for tumbler & Ceramic/Glass spittoon.
Single reflecting led sensor Operating Light with 2 intensity High & Low.
Modular under hang delivery system with 2 Airtor & inbuilt Micro motor Provision
Instrument Arm with Pneumatic Lock system with Large Instrument Tray.
2 Nos. of 3-Way Syringes (One for Assistant side).
Saliva Ejector with low suction.
LED Film Viewer white light.
Doctor's comfort Stool with Adjustable feature.



Laboz Dental Compressor

Horse Power 1 HP
Air Tank Capacity 35L/40L
Discharge Pressure 6-8 bar
Lubrication Style Oil Free
Compressor Noise Level 52 DB (A)
Power 750W
Coating Epoxy coated
Medical grade Air



Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369



Laboz Inc

Scalar UDS-A (LED)

Automatic frequency tracking ensure that machine Always works on the best frequency and performs more steadily . the hand piece is detachable and can be autoclaved to the high temperature of 135 C and the pressure of 0.22Mpa.Digitally controlled easy operation and more Efficient for scaling .Comes in LED variant
Power Source Input: 220-240 V.
Output Half-Excursion Force: Less Than 2 N.
Frequency: 28 kHz+/- 3 kHz.
Output Power: 3W to 20W.
Water Pressure : 0.1bar to 5bar (0.01MPa to 0.5MPa)
Protection Against Electric Shock: Class II.



D1 Scalar

Sealed handpiece.
Automatic frequency tracking.
Automatically search the best working frequency.
Two colours optional.
Power input 110V~ 50Hz/60Hz.
220 - 240V~ 50Hz/60Hz.
Main unit input 24V~ 1.3A.
Output power 3W~20W.



UDS J Scalar

Woodpecker ultrasonic scaler UDS J is a scaler with Sealed hand piece with Automatic frequency tracking system which automatically searches for the best working frequency. It has a feature of Automatic degenerative feedback with constant power output, which provide more comfortable scaling.

- The handpiece is cast of Titanium alloy to ensure sound mechanical function and durability.
- The cable is of silica gel tube, which is soft and durable.
- The cavitation produced at the end of scaling tip helps in easy cleaning of the



Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369



Laboz Inc

Technical Specifications:

Main unit input 24V-50Hz/60Hz 1.3A
Output power 3W-20W
Frequency 28kHz \pm 3kHz
Water pressure 0.1bar ~ 5bar(0.01MPa ~ 0.5MPa)
Main unit weight 1kg
Dimensions 198mm×134mm×80mm

MODEL:LUX C

Wireless

- .The battery can be replaced
- .3 work modes full ramping pulse
- .time setting :5s – 20s (Incremental)
- .Large capacity battery (400 times use) low Standby power consumption with forty days Standby time
- .Constant right intensity



Woodpecker LUX E Plus Curing Light

Power input: AC100V-240V50Hz/60Hz.
Main unit weight: 147g.
Light intensity: 1000mW/cm²-1200mW/cm².
Dimensions: 263mm×40mm×50mm.
Light output area : 800mW/cm - 1600mW/cm².
LUX E Plus solidifies 4mm deep resin in 3 Seconds.
Large capacity battery. A full charge can be used for more than 300 times continuously 10s working time mode.
Low standby power consumption with twenty days standby time. Constant light intensity.
The solidification effect is not affected by the consumption of remaining power.
Power point indicator. Long Life LED.



Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369



Laboz Inc

Dental autoclave (front Loading) LI-0071 Table top front loading autoclave, unit is fully automated

microprocessor controller based. Sterilization chamber is made of S.S Sheet, tested for high pressure. Digital timer for both wet and dry cycles. Auto drain of water reservoir tank and also condensation of steam available. Alarm system calls after total cycle completion. Working temperature 121°C and 134°C. To work on 220/230v, single phase AC supply.



Autoclave portable LI-0051

Single walled complete S.S/ Aluminum body, seamless as per specification. Electrically operated. Complete with MS powder coated stand, Pressure gauge, Pressure release valve, safety valve. To work on 220/240V ,Ac ,Single phase supply
Dia x Depth
300x300mm
300x375mm
350x400mm
300x500mm



Laboz Air Rotor hand Piece

We are the leading supplier of Stainless Steel Dental Handpiece
Ergonomic Design
working Air Pressure 0.22-0.3Mpa
Ceramic bearing
available connection 02 hole
Noise less than 65 dB
Autoclavable
Speed: High Speed
Body Material: Stainless Steel
Speed Range: 370, 000 - 430, 000 RPM



Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369



Laboz Inc

Laboz UV Chamber

UltraViolet Chambers with advanced technology and enhanced ability for maintaining the sterilization after the instruments have been sterilized by autoclave or sterilizer.

It is equipped with high quality Ultraviolet Light for its effective functioning. UV Chamber is epoxy coated Ultraviolet chamber with 12 tray capacity.

Features

Fine Epoxy powder coated matte finish

The inner chamber is made with rust proof stainless steel bright mirror finish sheet which reflects the UV rays to pass uniformly through entire work surface area within the cabinet

12 plastic autoclavable trays

Works with UV Light source

Magnetic gasket on the door seals the chamber

Micro door switch immediately cuts off the UV source when the door is opened, preventing accidental UV exposure.

Rust Free

Corrosion Resistant



Laboz Glass Bead Sterilizer

Glass Bead Sterilizer is used in dental clinics for effectively sterilizing small dental instrument. WARRANTY " Manufacturer/Importer warranty of 12 Months applicable for this product. " Service and Warranty are handled by the manufacturer/importer directly for this product.

Product Type : simple



Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369



Laboz Inc

Laboz Dental Boiler

Water boiler is great for reduction of bacteria, viruses and protozoa is desired.
Advantages:

- Consumable.
- Time saving.
- Energy Saving
- 24-84 GPM (gallons per minute) flow.
- Great for reducing of bacteria and viruses.
- Easy to use.
- Optimum efficiency.



Dental X ray

X Ray is compatible with all the digital sensors currently on the market.
for those that prefer a no-frills unit, dent-X is the best tradeoff between performance and budget.

To adapt to every installation condition, dent-X can be configured with a remote X-ray pushbutton that allows you to start the exposure outside the examination room.

The mobile version will give the maximum positioning freedom.



Specification

- Power Supply 230V +/- 10 %
- X-Ray tube 70kV, 10mA
- Focal spot 0.8mm x 0.8mm
- Focus to the skin distance 20 cm.
- Filtration 1.5 -Al
- Exposure times 0.1s to 2.99 s
- Anatomic programs (Optional)
- 30 pre- set times with cordless remote
- Micro processor base timer with cordless remote for time setting and exposure

Reg Off: D8/6, DLF Ankur Vihar, Ghaziabad, U.P-201102

labozinc.com,labozincsales@gmail.com,info@labozinc.com,8860356096,9136440369