



HIGH PRESSURE PLUNGER PUMP

"Malhar" High-Pressure (simplex / duplex / triplex / sixplex) plunger pump is a positive displacement pump. which can deliver high flow stream at high pressure with high efficiency. These pumps are also know as hydro test pump, pressure test pump, hydrostatic test pump.

OPERATING RANGE

- **Flow Range** : Up to 30,000 LPH
- **Pressure Range** : Up to 1000 Kg / Cm²
- **Temperature Range** : 30°C / TO 300°C
- **M.O.C** : AISI 316, AISI 304, AISI 410, CS, ALLOY-20 , HASTELLOY C & B, TITANIUM, MONEL, ETC
- **Wet And Cartridge** : Single / double acting (simplex / duplex / triplex / pentaplex) plunger
- **Valve** : Ball, Cone, Plate , Wing with or without spring loaded
- **Gland Packing** : U seal (PTFE, CHEVRON, PU) / Square rope.
- **Options** : Pressure relief valve, Pulsation Damper, Instrumentation and automation, completer Pumping systems

APPLICATION

- Airport & Ship Yards.
- Railway Workshop & Cleaning Yards.
- State Transport & Workshop.
- Industrial & Agriculture Purpose.
- Auto Two & Four Wheel Workshop for washing /cleaning application.
- RO water and sea water high pressure application.

