

Ultrasonic High Tech Equipments

For Industrial Cleaning, Welding, NDT, Fabric Cut & Seal, Sieving, Sonochemical Processing

Overview

ROOP ULTRASONIX LTD (RTUL) is a leader in design, development, manufacture and marketing of a wide range of Ultrasonic Machines. It has the most modern manufacturing facilities at Gandhinagar in Gujarat, and Mumbai, with well equipped application laboratory, tool room and machine shop, sophisticated testing and designing center and high-tech measuring instruments. Apart from Mumbai and Gandhinagar, RTUL has its sales and service offices in Delhi, Chennai, Kolkata, Indore and has a well spread representative network in the country. The company's emphasis is always on delivering the latest ultrasonic to the industry. Constant upgradation of instruments through research keeps pace with the times. RTUL manufactures all its products with exceptional quality and value. The company's commitment to providing the very best customer service is evident from its continuing investment in manufacturing technology and productivity enhancing capital requirements.



PLASTIC WELDING ULTRASONIC WELDING MACHINE / SYSTEM

Joining of thermoplastic components and insertion of metal components in a with the help of this machine. Higher strengths, better finish, consistent quali

APPLICATION

Toys, Gifts & Novelty articles, Industrial components, Laminated foils and Tubes, Thermowares, Automobile Components & Lighting accessories.

SPECIAL FEATURES

- Energy & time mode selection
- Rigid, heavy duty pneumatic press
- Printing of welding data & calibration of parameters.
- ★ Self Diagnosis
- * Auto tuning of horn and horn life indication
- ★ Electronic amplitude setting
- ★ Easy upgradation and Automation

TECHNICAL SPECIFICATIONS

	UHG-500/1000	WP 10-500/1000	WP 750	WP 3000-1000/1500/2000/3000/4500	WP 3000/6000-3000/4500		
Pneumatic Press		WP 450	WP 750	WP 3000	WP 3000		
Closing Force Max.	-	450	750	3000	3000/6000		
Generator	HG-35-500/1000	WG-35-500/1000	WG-36-1000/WG-20-1500	WG-20-1000/1500/2000/3000/4500	WG-15-3000/4500		
Ultrasonic O/p Power (W)	500/1000	500/1000	1000/1500	1000/1500/2000/3000/4500	3000/4500		
O/p Frequency (KHz)	35	35	20/36	20	15		
Dimention- Press	Dia 54×220	$300 \times 500 \times 490$	360 imes 575 imes 1000	410×685×960	$410 \times 685 \times 960$		
(WxDxH)mm Generator	$500 \times 350 \times 220$	$93 \times 365 \times 278$	$510 \times 440 \times 220$	$510 \times 440 \times 220$	$510 \times 440 \times 220$		
Weight - Press	0.6/1.2	22	60	100	100		
(Kg) Generator	15	7.2	35	35	35		
Max. Stroke (mm)	-	50	100	100	100		
Throat Depth (mm)	-	80	150	275	275		
Working Table (WxD)m m		200 imes 300	300 imes 325	465×410	465×410		



PLASTIC WELDING

Powerhouse of Ultrasonic Technology

SPIN WELDING MACHINE

Joining of circular thermoplastic parts can be achieved by this friction welding technique. The machine operates at 100 to 4000 rpm with a robust press exerting a force of 2500 Newton.

APPLICATION

Specially useful for nylon and poly propylene circular parts like cream jar, bottle, oil containers etc.

METAL WELDING MACHINE

Joining of similar and dissimilar non-ferrous metals can be achieved with higher strength and better electrical and thermal conductance quality. Higher production rate with consistent quality is possible.

APPLICATION

Switchgears, electrical connectors, coils, solar panels, collectors for solar heating systems, telecommunication equipments.

FEATURES

- Welds similar and dissimilar non-ferrous material.
- Excellent weld quality and helium tight welding.
- ▶ Fast, reliable, consistent welding quality with microprocessor controller.
- No need of any filler materials.
- Low power consumption.
- ▶ Clean and safe process (no sparks, flames and smoke formation) and hence, environmental friendly.
- 100% bond conductance.
- Can be easily automated.
- Continuous welding operation possible.





ULTRASONIC ECO-SPLICER

All Good Things in One Machine

Roop Ultrasonix Ltd. offers high power/high precision equipment for wire splicing. Precision and reliability are decisive preconditions for electrical connections in automobile wire harness. Ultrasonic welding ensures flawless electrical conductivity in the wire splices over years and years.

FEATURES

- ★ Compact Machine-light weight
- * User-friendly for set up and operation.
- * Simple, fast and secure Tooling Change-over
- ★ Very stable and safe process
- ★ Software



Powerhouse of Ultrasonic Technology

${f T}_{ m extile}$ cutting and sealing system

Ultrasonic Cutting And Sealing System is used in the textile industry for cut & seal application in single operation. Particularly in the continuous cutting of synthetic fabrics composed of minimum 60% thermoplastic fibre like PP, polyethylene, polyester, nylon. The process offers definite advantage over previous methods such as sealing, clean cutting, fast processing time, extremely low rejection rates and low energy consumption.

ULTRASONIC CONTINUOUS CUTTING & SEALING SYSTEM

- ★ Woven Sacks (pp/hdpe)
- ★ FIBC(Straight & Circular Cutting)
- * Jumbo Bag (Straight & Circular Cutting)
- ★ Geo Textiles
- ★ Silt Fence
- ★ Industrial Fabrics
- ★ Tyre Cord Fabrics
- ★ Filter Fabrics (woven/non-woven)
- ★ Labels/ribbons Medical etc.
- ★ Sarees & ladies dress materials

UNIQUE FEATURES & ADVANTAGES

- * Automatic Tuning of Horn & Horn life indication
- ★ Built in electronic amplitude setting– allowing the user to choose amplitudes through generator between 70% to 100% without changing the Booster.



ULTRASONIC TPC SERIES COMPACT CLEANER

High intensity ultrasonic waves are used for degreasing/cleaning through cavitation effect. These compact table top cleaners are very versatile for all general purpose cleaning applications.

APPLICATION

Surgical and hospital equipments, watches, diamonds & jewellery, lenses & glass frames, PCB, industrial & mechanical components, bearings etc.

COMPACT CLEANER FEATURES

- ★ Multifrequency option available: 30/90/150KHz
- * Digital control of time and temperature
- ★ SS tank with complete SS body
- ★ Low noise level
- ★ Suitable for continuous operation
- * Rugged and easy to clean stainless steel housing
- ★ Fully transistorized generator
- * Automatic frequency tuning for maximum output.
- Independent of liquid level, temperature and/or parts to be cleaned
- ★ Maintenance-free
- ★ Latest technology
- ★ Universal application

ULTRASONIC COMPONENTS FOR CLEANER/ CLEANING SYSTEM

IMMERSIBLE BOX

This is available in different sizes, with different output power Frequency: 20, 30, 40, 80, 120, 150 KHz Power: 600, 750, 1000, 1200, 1500 Watts



COMPACT CLEANERS

MODEL	US Output Watts	Vol. Litres	Inside Tank Dim (mm) L x W x H
TPC-15	75	1.5	150 x 135 x 100
TPC-25	100	2.5	235 x 135 x 100
TPC-40	150	4.0	235 x 135 x 150
TPC-120	300	12.0	300 x 235 x 200
TPC-280	600	28.0	505 x 300 x 200
IUC-50	750	50	550 x 350 x 300
IUC-70	1000	70	600 x 400 x 350
IUC-110	1200	110	700 x 450 x 400
IUC-170	1500	170	800 x 500 x 500
IUC-250	2000	250	1000 x 500 x 600





ECO GENERATOR

- * Suitable for large output powers
- Designed for tube resonators, immersing transducers and transducer plate fitted to tanks
- * Optional communication via RS-232 interface
- ★ Three free programmable relay outputs
- ★ Five DC-isolated 24V inputs, for external power setting for instance
- ★ Over-temperature and over-current turn off
- ★ Protected against short-circuit and no-load operation
- ★ Coefficient of efficiency >90%
- ★ Fully automatic control and monitoring
- ★ Table top housing, 19" rack mounted version, DIN-rail mounting or wall fastening



TUBE RESONATOR

 This novel design of transducer in tubular form ensures ultrasonics in all 360 direction and ease in retrofitting in existing system. This is available in various frequencies and different mounting lengths. Length: 476-1139 mm
 Frequency: 20, 25, 40, 80, 100 & 120 KHz

Power: 300, 500, 600, 750, 1000 & 1500 Watts

- * Very intensive and homogeneous sound field due to 360° radiation
- * Low weight and volume allows mounting in confined spaces
- * Possible to mount in pressure and vacuum tanks
- * No dirt deposit onto the radiation surface
- ★ Ideal for retrofit in existing tanks
- * Multiple application, thanks to different mounting lengths
- * Low power consumption due to high coefficient of efficiency (>92%)
- ★ Suitable for large output powers

CUSTOM BUILT CLEANING SYSTEM

For large cleaning volumes and high degree of cleanliness level, either large capacity single tank systems or multi-chamber systems are offered with solvent or water based cleaning media, complete with recirculation, filtration and material handling system. Various models with aqueous, hydrocarbon or solvent based cleaning media are available.





ULTRASONIC TESTING

FLAW DETECTOR-MODEL 4444D

Ultrasonic flaw detectors detect internal flaws such as cracks, blow holes etc. They can also be used for finding out elastic constant and correlating sonic velocity to mechanical parameters.

APPLICATION

For casting, forging and rolled products, weld inspection, bond testing, automatic immersion testing for tubes and rods, research and laboratory studies. The model is light weight, portable, battery operated and conform to international standards.



SPECIAL FEATURES OF 4444D

- ★ Bright High Resolution TFT Display.
- ★ Battery Life: 8 hrs.
- ★ DAC with Alarm, Dual Gate, B Scan, Video Mode.
- ★ USB Port, RF output.

THICKNESS GAUGE

Three different models of Ultrasonic Thickness Gauge are offered to suit different areas of application. All these are suitable mostly where only one side access is available.

APPLICATION

- * For thickness measurement in tubes, plates and corrosion monitoring in pipes, vessels etc.
- * Automated systems for online thickness measurement in pipes or plates.

FEATURES

- ★ Light weight, easy to use
- ★ Thickness measurement for one side access components
- ★ On line thickness monitoring, with suitable fixtures
- ★ Microprocessor controlled with facility to store calibration and measured data and RS232 output for connection to computer.

MODEL	Transducer Type	Range mm.	Accuracy mm
4510	Dual	1.2-50	0.1
UX 4560	Dual	0.65-600/3-100	0.01

CONCRETE TESTER 4600L/4600LG/4605µ

Sonic velocity is used to assess strength and homogeneity of concrete and also to detect internal voids and cracks.

APPLICATION

For assessment of *in situ* and precast concrete structure; for homogeneity and strength; damage of structure due to fire etc. **FEATURES**


- ★ Light weight, easy to operate.
- * Range upto 5 meters with suitable probe
- ★ Fast, Reliable results.
- ★ Computer compatible
- \star Available in three models.
 - Basic
 - Microprocessor Controlled(M)
 - With Graphic Display(G)

TRANSDUCERS

Transducers for various applications from 25KHz to 25MHz are available in various sizes and types with different types of connectors. Corresponding cables can also be supplied.










CONCRETE TESTER

Powerhouse of Ultrasonic Technology

Ultrasonic processor / reactor

Processing of liquids for various reactions like emulsification, homogenization, cell disruption/extraction can be done by Ultrasonic. Laboratory models, pilot plants and production units available in various capacities.



Ultrasonic sieve deblinding attachment ("ultrascreen")

ULTRASCREEN deblinding attachment facilitates in improving/increasing output, efficiency in powder sieving through vibroscreens. Due to increased through-put process speed can also be increased and cost of vibroscreens, spares, labour, power can be reduced.



Tel: 044-24354384	Tel: 09004023199	Tel: 09825007609	Tel: 09845129401
<u>Exports:</u> Tel: +919820321390 Email : exports@rooptelsonic.com	Thailand: +66 27 413835	Malaysia: +60 16 3314980	Vietnam: +84 913081929

ROOP ULTRASONIX LIMITED

Regd. Off : A/41, Nandkishore Industrial Estate, Off Mahakali Caves Road, Andheri (E), Mumbai - 400 093. Corporate Office : 803,C Wing, 32 Corporate Avenue, Off Mahakali Caves Road, Andheri (E), Mumbai - 400093. Tel: 022-42111500 Fax : 42111505 E-mail: sales@rooptelsonic.com Web: www.rooptelsonic.com

RTUL